



Providing Solutions in Pressure Sensitive Films

Product Construction Sheet

THERMLfilm® Select 22830

GENERAL DESCRIPTION:

This is a topcoated thermal transfer printable silver matte polyester film coated with a permanent pressure sensitive acrylic adhesive and backed with a kraft release liner.

UL RECOGNITION:

This product is UL recognized for indoor/outdoor use with occasional exposure to lubricating oil and water. For further information, please reference FLEXcon's UL file No MH10170 (N) and MH16635 (N) or contact your FLEXcon Representative.

Table with 3 columns: PRODUCT DATA, VALUE, TEST METHOD. Rows include PHYSICAL PROPERTIES such as Thickness (micron) and Dimensional Stability (%).

ADHESION PROPERTIES\*\*

Table with 3 columns: Adhesion from (N/m), Average, and TEST METHOD. Rows include Adhesion from Stainless Steel, Acrylic, Glass, Expected Shear (hours), and Tack (gm/sq cm).

\*\* For guidance only
This data is based on limited test results due to the custom nature of this product, not to be used for setting specifications.

Table with 2 columns: PROPERTY and VALUE. Rows include EXPECTED EXTERIOR LIFE, SERVICE TEMPERATURE RANGE, MINIMUM APPLICATION TEMPERATURE, and STORAGE STABILITY.

\* THERMLfilm is a registered trademark of FLEXcon Company, Inc. 25/05/2004

Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product.